Version: V1.2

MSDS

MATERIAL SAFETY DATA SHEET

Prepared For

: ShenZhen HengLi Technology Co., Ltd.

11F., Bldg. C, SongGang Sub-Park, TaoHuaYuan Science and

Technology Innovation Park, Baoan District, ShenZhen City, China

Prepared By

: Shenzhen LCS Compliance Testing Laboratory Ltd.

101, 601, Xingyuan Industrial Park, Gushu Community, Xixiang Street,

Bao'an District, Shenzhen, Guangdong, China

Issue Date

: 2019.05.27

Report Number : LCS190416116ASD

Written by: ______ Una. Quan

Approved by:



REPORT NO.: LCS190416116ASD

* The MSDS is prepared based on the information provided by client. The contents and formats of this MSDS are revised as per client's request.

•	Section 1-Chemical Product and Company Identification				
Model	Lithium-ion rechargeable battery				
	HLB-3S3P				
Trade Mark	N/A				
Ratings	11.1V, 10500mAh, 116.55Wh				
Weight	451.7g				
Manufacturer	ShenZhen HengLi Technology Co., Ltd. 11E Ridg C SongCong Sub Park TooHuaYuan Science and Technology Innovation				
Manufacturer address	11F., Bldg. C, SongGang Sub-Park, TaoHuaYuan Science and Technology Innovation Park, Baoan District, ShenZhen City, China				
Emergency Telephone	+86-755-29892633				
Fax	+86-755-29892733				
Section 2- Composition Information					
Chemical Composition	(CAS No.	Weight (%)	Trade Secret	
Lithium cobaltate	12190-79-3		15 - 40	*	
Graphite	7782-42-5		10 - 30	*	
Phosphate(1-), hexafluoro-, lithium	21324-40-3		10 - 30	*	
Copper	7440-50-8		7-13	*	
Aluminium	7429-90-5		5-10	*	
Nickel	7440-02-0		1-5	*	
" * " The exact	percentage	(concentration) of c	omposition has been withheld	d as a trade secret.	
Section 3- Hazards Identification					
Emergency overview:		N/A			
Classification according	to GHS	Not a dangerous substance according to GHS			
Label elements:	Label elements:				
Hazard pictogram(s)		Not Available			
Signal word		Not Available			
Hazard statement(s)		Not Available			

REPORT NO.: LCS190416116ASD

Precautionary statement(s):		
Prevention	Not Available	
Response	Not Available	
Disposal	Not Available	
Environmental hazards:	No relevant information	
Important symptoms:	See section 11 for more information	
Section 4- First Aid Measures		
Eye contact	Flush eyes with plenty of water for least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.	
Skin contact	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.	
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.	
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.	
Section 5- Fire Fighting Measures		
Flash Point	N/A	
Auto-Ignition Temperature	N/A	
Extinguishing Media	H ₂ O, CO ₂	
Special Fire-Fighting Procedures	Self-contained breathing apparatus	
Unusual Fire and Explosion Hazards	Cell may vent when subjected to excessive heat-exposing battery contents	
Hazardous Combustion Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.	
Ocation C. Assidental Delegas Massaures		

Section 6- Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed with sand, earth or other inert substance and contaminated area should be ventilated meantime.

Environment precautions:

Do not allow product to reach sewage system or any water source.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

REPORT NO.: LCS190416116ASD

Methods and material for containment and cleaning up:

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

Section 7- Handling and Storage				
Handling	The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.			
Storage	Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.			
Other Precautions	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.			
Section 8- Exposure Controls/Personal Protection				
Engineering Controls	Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.			
Personal Protective Equipment	Respiratory Protection: Not necessary under normal conditions. Skin and body Protection: Not necessary under normal conditions, Wear suitable protective clothing and gloves if handling an open or leaking battery. Hand protection: Wear suitable gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.			
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.			
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.			
Section 9- Physical and Chemical Properties				
Form	Solid			
Color	Blue			
Odour	Not Available			
рН	Not Available			

REPORT NO.: LCS190416116ASD

Melting point/freezing point	Not Available	
Boiling Point and Boiling range	Not Available	
Flash Point	Not Available	
Upper/lower flammability or explosive limits	Not Available	
Vapor Pressure	Not Available	
Vapor Density	Not Available	
Relative density	Not Available	
Solubility in Water	Not Available	
Auto-ignition temperature	Not Available	
Decomposition temperature	Not Available	
Evaporation rate	Not Available	
Flammability (soil, gas)	Not Available	
Viscosity	Not Available	
Section 10- Stability and reactivity		
Stability	The product is stable under conditions described Section 7	
Conditions to Avoid	Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions.	
Incompatible Materials	Oxidizing agents, acid, base.	
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.	
Possibility of Hazardous Reaction	Not Available	
Section 11 – Toxicological Information		
Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.	
Sensitization	Not Available	
Neurological Effects	Not Available	
Teratogenicity	Not Available	
Reproductive Toxicity	Not Available	

REPORT NO.: LCS190416116ASD

	REPORT NO LCS 1904 TO TRASE			
Mutagenicity (Genetic Effects)	Not Available			
Toxicologically Synergistic Materials	Not Available			
Section 12- Ecological Information				
Ecological Toxicity	Not Available			
Mobility in soil	Not Available			
Persistence and Degradability	Not Available			
Bioaccumulation potential	Not Available			
Other Adverse Effects	Not Available			
Section 13- Disposal Considerations				
Product disposal recommendation	Observe local, state and federal laws and regulations.			
Uncleaned packaging recommendation	Disposal must be made according to official regulations			
Section 14 – Transport Information				
Label for conveyance	Lithium Battery Label			
UN Number	UN 3480 or UN 3481			
Transport hazard class(es)	9			
Packing group	II			
Marine pollutant	No			
UN Proper shipping name	Lithium ion Batteries (Including lithium ion polymer batteries) Lithium ion Batteries packed with equipment (Including lithium ion polymer batteries) Lithium ion Batteries contained in equipments (Including lithium ion polymer			
Transport information:	batteries)			

Transport information:

Lithium-ion rechargeable battery (Sample Model: HLB-3S3P) is tested and has passed in accordance with UN manual of Tests and Criteria, Part III, subsection 38.3.

The goods shall be complied with the requirements of Section IA of Packing Instruction 965 or of Section I of Packing Instruction 966 967 of 60th DGR Manual of IATA or IMDG CODE (Amdt. 39-18).

Separate Lithium-ion batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport, ensure that the goods will not falling, dropping, and breakage, Prevent collapse of cargo piles and wet by rain.

Transport Fashion: By air, by sea, by railway, by road.

REPORT NO.: LCS190416116ASD

Section 15- Regulatory information

Law information

《Dangerous Goods Regulations》

《Recommendation on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous Goods》

《Occupational Safety and Health Act》(OSHA)

《Toxic Substance Control Act》(TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》(SARA)

《Resource Conservation and Recovery Act》(RCRA)

《Safety Drinking Water Act》(CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In according with all Federal, State and local laws.

Section 16- Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, concorde makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

-- End of Report --