ISOJET/42 (BLUE)

PRESSURE WASH - BLUE VERSION



TECHNICAL DATA

PART REF.	HOSE SIZE			R.O.D		O.D		MAX. W.P		BURST		MIN. BEND		WEIGHT		FITTINGS	
	DN	dash	inch	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	g/m	lb/ft	Std 1	Std 2
H01193006*	6	-4	1/4"	11.2	0.44	13.2	0.51	420	6,090	1,260	18,275	50	1.96	258	0.17	MF + M03400-04	
H01193008*	8	-5	5/16"	13	0.51	15	0.59	420	6,090	1,260	18,275	55	2.16	316	0.21	MF + M03400-05	
H01193010*	10	-6	3/8"	14.6	0.57	16.8	0.66	420	6,090	1,260	18,275	65	2.55	372	0.25	MF + M03400-06	
H01193012*	12	-8	1/2"	18.6	0.73	20.6	0.81	420	6,090	1,260	18,275	90	3.54	521	0.35	MF + M03450-08	

KEY FEATURES

- Wrapped surface
- Indelible branding
- Compact structure: easy handling, reduced bend radius
- Good abrasion resistance
- Safety Factor 3:1

APPLICATIONS & FLUIDS

- Water-cleaning equipment, ideal for hobby and semi-professional machines
- Water, mineral oils, vegetable and rape seed oils, glycol and polyglycol based oils, synthetic ester based oils, oils in aqueous emulsion

CONTINUOUS SERVICE TEMPERATURE RANGE

-10 °C, 15 °F

135 °C, 275 °F

TUBE

Water resistant synthetic rubber

REINFORCEMENT

Two high tensile steel braids

COVER

Weather resistant synthetic rubber

APPLICABLE SPECS

Manuli® Design

manuli® HYDRAULICS

INDUSTRIAL