


|                               |   |   |
|-------------------------------|---|---|
| Type no.                      | 570 44  |   |
| Article no.                   | 010570440101                                  |   |
| Standards                     | DIN EN 50342-1, 50342-2                       |   |
| Application                   | Starter battery                               |   |
| <b>Electrical data</b>        |   |   |
| Rated voltage                 | 12V   |   |
| Rated capacity                | 70 Ah (K20)                                   |   |
| Cold start current            | 640 A (EN)                                    |   |
| <b>Dimensions and weights</b> |   |   |
| Box                           | T6  |  |
| Length max.                   | 278mm   |   |
| Width max.                    | 175mm   |   |
| Box height max.               | 175mm   |   |
| Total height max.             | 175mm   |   |
| Battery weight                | Ca. 17,0 kg (+/- 5 %)                         |   |
| Electrolyte density           | Approx. 1,28 kg/l                             |   |
| Electrolyte                   | Diluted sulphuric acid                        |   |
| Items/pallet                  | 64  |   |
| Pallet ID                     | Euro pallet                                   |   |
| Items per layer               | 16  |   |
| <b>Features</b>               |   |   |
| Base hold-down                | B13   |   |
| Layout                        | 0   |   |
| Terminal                      | 1   |   |
| Separator                     | PE bag separator                              |   |
| Degassing                     | Battery with central degassing                |   |
| Flame arrester                | Integrated                                    |   |
| Performance identification    | W4 - C2 - V1 - E1                             |   |
| <b>Maintenance 1)</b>         |   |   |
| Water consumption             | W4  |   |
| Refill water                  | Destilliert oder entmineralisiert (DIN 43530) |   |
| Self-discharge                | Ca. 3 % pro Monat                             |   |
| Charging current              | Ca. 1/10 der Nennkapazität                    |   |
| Charging voltage 2)           | max. 14,8 V                                   |   |

1) All the listed values relate to room temperature +25° C

2) Recommendation with an external, voltage-regulated charge. Attention: Temperature compensation in case of deviation!

1 Document DBTBAT00339 prepared on 2018-04-01 ; Rights relating to changes and errors retained.  
original