

---

**DATA SHEET**  
**for PREMIUM 75 Ah**  
According to EN 50342  
Date of updated: 29.08.2016

---

**ePM 12V - 80 Ah / L77L3K3 1**

**Electrical specification**

Voltage:  (V)  
Capacity:  (Ah)  
Cold cranking current:  (A, EN)  
Cold cranking current:  (A, DIN)

**Mechanical specification**

Dimensional group:  EN50342-2:2009  
ETN reference:   
OB reference:   
Sizes:  (L x W x H)  
Cell Layout:   
Terminal Type:

---

<b><u>Container</u></b>	<u>Case</u>	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
		Bottom hold down	<input type="text" value="B13"/>	Handles	<input type="text" value="-"/>
	<u>Lid</u>	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
		Cover design	<input type="text" value="KAMINA"/>	Handles	<input type="text" value="BLACK"/>
	<u>Vent cap</u>	Material	<input type="text" value="POLYPROPYLENE"/>	Colour	<input type="text" value="BLACK"/>
		Type	<input type="text" value="KAMINA"/>		

---

**Test details**

Vibration resistance:   
Endurance resistance:

---

Battery weight:  ± %5 (kg)  
Acid weight:  ± %5 (kg)  
Total battery weight:  ± %5 (kg)

---

**Separator:** Type:

---