

SAFETY DATA SHEET

Product: Li-ion Battery Pack

Model/type reference: BCL1B03IB

Nominal Voltage: 14.4V

Rated Capacity: 2.5Ah (36Wh)

Applicant: DONGGUAN KOHAM INDUSTRIAL CO., LTD.

Address: NO. 1, ShaHu Road, Shahu County, Tangxia Town, Dongguan City, Guangdong Province, CHINA. P. C. 523725

Report No: P22120818401

Effective date: 2024-02-15

Revision date: 2024-02-15

Laboratory: **Shenzhen NTEK New Energy Technology Co., Ltd.**

Room 101, Building C, Fenda Hi-Tech Park, Sanwei Community, Hangcheng Subdistrict, Bao'an District, Shenzhen, Guangdong, China.

The supplier identified below generated this SDS using the NTEK SDS template. NTEK did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publicly available regulatory data sources. NTEK makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS.

Compiled by (name+ signature) ...: Snow Liu

Snow Liu

Approved by (name+ signature) ...: Jesse Zhang

Jesse Zhang

Section 1- Identification of the Substance/Preparation and of the Company/Undertaking

Product Identifier

Product Name: Li-ion Battery Pack

Model No.: BCL1B03IB

Other means of identification

Synonyms: None

Recommended use of the chemical and restrictions on use

Recommended Use: LITHIUM ION BATTERIES

Uses advised against: No information available

Details of the supplier of the safety data sheet

Manufacturer's/ Supplier Name: Dongguan iRice Electronics Development Co., Ltd.

Address: No. 9 Hudie 1st Road, Tianxin Village, Huangjiang Town, Dongguan City, China

Telephone number of the manufacturer/supplier: +86-769-83638899

Emergency Telephone Number (24h): +86-769-83638899

E-mail address: bw_qiu@iricepower.com

Version number: V2.0

Section 2 – Hazards Identification

Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) this product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1
Specific target organ toxicity (repeated exposure)	Category 1

GHS Label elements, including precautionary statements

Emergency Overview

Signal word: Danger

Hazard Statements

Causes skin irritation

Causes serious eye irritation

May cause an allergic skin reaction

May cause cancer



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold.

Intended use of the product should not result in exposure to the chemical substance. This is a battery. In case of rupture: the above hazards exist.

Appearance Black and Orange

Physical State Solid

Odor Odorless

Precautionary Statements - Prevention	Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Contaminated work clothing should not be allowed out of the workplace Wear protective gloves Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product
Precautionary Statements - Response	IF exposed or concerned: Get medical advice/attention Specific treatment (see supplemental first aid instructions on this label) IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water Take off contaminated clothing and wash before reuse If skin irritation or rash occurs: Get medical advice/attention
Precautionary Statements - Storage	Store locked up
Precautionary Statements - Disposal	Dispose of contents/container to an approved waste disposal plant
Hazards not otherwise classified (HNOc)	Not applicable
Unknown Toxicity	-
Other information	May be harmful if swallowed Very toxic to aquatic life with long lasting effects Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
Interactions with Other Chemicals	No information available.

Section 3 – Composition/Information on Ingredients

Chemical Name	CAS Number	Weight-%	Trade Secret
Lithium Nickel Oxide	12325-84-7	25~35	-
Graphite	7782-42-5	20~30	
Iron	7439-89-6	10~20	-
Copper	7440-50-8	5~15	-
Lithium cobaltate	12190-79-3	1~5	-
Methyl propionate	554-12-1	1~5	-
Aluminium	7429-90-5	1~5	-
Lithium hexafluorophosphate	21324-40-3	1~3	-
4-Fluoro-1, 3-dioxolan-2-one	114435-02-8	1~3	-
Dimethyl carbonate	616-38-6	1~3	-
Polyethylene	9002-88-4	1~3	-
Ferric oxide	1309-37-1	0.1~1	-
BOEHMITE	1318-23-6	0.1~1	-
Carbon Black	1333-86-4	0.1~1	-
Nickel	7440-02-0	0.1~1	-
1-Methyl-2-pyrrolidinone	872-50-4	0.1~1	
Aluminum lithium oxide (AlLiO)	11089-89-7	0.1~1	
Chromium	7440-47-3	0.1~1	
Lithium carbonate	554-13-2	0.1~1	
Ethylbenzene	100-41-4	0.1~1	

* The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4 – First-aid Measures

General Advice	<p>First aid is upon rupture of sealed battery.</p> <p>Eye contact: If symptoms persist, call a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Do not rub affected area.</p> <p>Skin contact: Wash off immediately with soap and plenty of water for at least 15 minutes. In the case of skin irritation or allergic reactions see a physician. May cause an allergic skin reaction.</p> <p>Inhalation: Remove to fresh air. If symptoms persist, call a physician. Get medical attention immediately if symptoms occur.</p> <p>Ingestion: Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician.</p>
----------------	---

	Self-protection of the first aider: Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).
Most important symptoms and effects, both acute and delayed	Most important symptoms and effects: Itching. Coughing and/ or wheezing.
Indication of any immediate medical attention and special treatment needed	Notes to Physician: Treat symptomatically. May cause sensitization of susceptible persons.

Section 5 – Fire-fighting Measures

Suitable extinguishing Media	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing Media	CAUTION: Use of water spray when fighting fire may be inefficient.
Specific Hazards arising from the chemical	Product is or contains a sensitizer. May cause sensitization by skin contact.
Hazardous Combustion Products	Carbon oxides.
Explosion Data	Sensitivity to Mechanical Impact: No. Sensitivity to Static Discharge: No.
Protective Equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 – Accidental Release Measures

Personal Precautions, protective equipment, and emergency procedures	Personal Precautions: Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Other Information: Refer to protective measures listed in Sections 7 and 8.
Environmental Precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.
Methods and material for containment and cleaning up	Methods for Containment: Prevent further leakage or spillage if safe to do so. Methods for cleaning up: Pick up and transfer to properly labeled containers.

Section 7 – Handling and Storage

Precautions for safe handling	Handling: In case of rupture. Use personal protection equipment. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray.
Conditions for safe storage, including any incompatibilities	Storage: Keep containers tightly closed in a dry, cool and well-ventilated place. Incompatible Products: Strong acids. Strong oxidizing agents. Strong bases.

Section 8 – Exposure Controls and Personal Protection

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Graphite 7782-42-5	TWA: 2 mg/m ³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m ³ total dust synthetic TWA: 5 mg/m ³ respirable fraction synthetic (vacated) TWA: 2.5 mg/m ³ respirable dust natural (vacated) TWA: 10 mg/m ³ total dust synthetic (vacated) TWA: 5 mg/m ³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m ³ TWA: 2.5 mg/m ³ respirable dust
Copper 7440-50-8	TWA: 0.2 mg/m ³ fume TWA: 1 mg/m ³ Cu dust and mist	TWA: 0.1 mg/m ³ fume TWA: 1 mg/m ³ dust and mist (vacated) TWA: 0.1 mg/m ³ Cu dust, fume, mist	IDLH: 100 mg/m ³ dust, fume and mist TWA: 1 mg/m ³ dust and mist TWA: 0.1 mg/m ³ fume
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	-
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	TWA: 0.02 mg/m ³	-	-
Nickel	TWA: 1.5 mg/m ³	TWA: 1 mg/m ³ (vacated)	IDLH: 10 mg/m ³

7440-02-0		TWA: 1 mg/m ³	TWA: 0.015 mg/m ³
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Aluminum 7429-90-5	TWA: 1 mg/m ³ respirable fraction	TWA: 15 mg/m ³ total dust TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 15 mg/m ³ total dust (vacated) TWA: 5 mg/m ³ respirable fraction (vacated) TWA: 5 mg/m ³ Aluminum	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust

*ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA

PEL: Occupational Safety and Health Administration - Permissible Exposure Limits NIOSH IDLH Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls	Engineering Measures: Showers Eyewash stations Ventilation systems.
Individual protection measures, such as personal protective equipment	Eye/Face Protection: If splashes are likely to occur: Wear safety glasses with side shields (or goggles). None required for consumer use. Skin and Body Protection: Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves. Respiratory Protection: No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Hygiene Measures: Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Wash hands before breaks and immediately after handling the product.

Section 9 - Physical and Chemical Properties

Physical Properties	Physical state: Solid
	Appearance: Black and Orange, Prismatic
	Color: Black and Orange
	Odor: Odorless
	Odor Threshold: No information available

Chemical Properties:

Property	Values	Remarks/ Method
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	No data available	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air	No data available	
Upper flammability limit	No data available	
Lower flammability limit	No data available	-
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Specific Gravity	No data available	None known
Water Solubility	Insoluble in water	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	0.00001	None known
Autoignition temperature	130°C	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	0.00001	None known
Explosive properties	No data available	-
Oxidizing Properties	No data available	-

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	No data available

Section 10 - Stability and Reactivity

Reactivity	No data available.
Chemical stability	Stable under recommended storage conditions.
Possibility of Hazardous Reactions	None under normal processing.
Hazardous Polymerization	Hazardous polymerization does not occur.
Conditions to avoid	None known based on information supplied.
Incompatible materials	Strong acids. Strong oxidizing agents. Strong bases.
Hazardous Decomposition Products	Carbon oxides.

Section 11 - Toxicological Information

Information on likely routes of exposure

Product Information	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:.
Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.
Eye Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.
Skin Contact	Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Graphite 7782-42-5	> 10000 mg/kg (Rat)	-	-
Iron 7439-89-6	= 984 mg/kg (Rat)	-	-
Nickel 7440-02-0	> 9000 mg/kg (Rat)	-	-
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-

Information on toxicological effects	Symptoms: Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives.
Delayed and immediate effects as well as chronic effects from short and long-term exposure	Sensitization: May cause sensitization of susceptible persons. May cause sensitization by skin contact. Mutagenic Effects: No information available.

		Carcinogenicity: The table below indicates whether each agency has listed any ingredient as a carcinogen		
--	--	---	--	--

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	A3	Group 2B	-	X
Nickel 7440-02-0		Group 1 Group 2B	Reasonably Anticipated	X
Carbon black 1333-86-4	A3	Group 2B	-	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A1 - Known Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).
Chronic Toxicity	Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Vascular System (CVS).Kidney. Liver. Lungs. Heart.
Aspiration Hazard	No information available.

Numerical measures of toxicity Product Information

The values which are on the right are calculated based on chapter 3.1 of the GHS document.	ATEmix (oral) ATEmix (dermal) ATEmix (inhalation-dust/mist)
--	---

Section 12 - Ecological Information

Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper 7440-50-8	96h EC50: 0.031 - 0.054 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 0.0426 - 0.0535 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 0.0068 - 0.0156 mg/L (Pimephales promelas) 96h LC50: 0.112 mg/L (Poecilia reticulata) 96h LC50: 0.3 mg/L (Cyprinus carpio) 96h LC50: 0.8 mg/L (Cyprinus carpio) 96h LC50: 1.25 mg/L (Lepomis macrochirus) 96h LC50: 0.052 mg/L (Oncorhynchus mykiss) 96h LC50: 0.2 mg/L (Pimephales promelas) 96h LC50: < 0.3 mg/L (Pimephales promelas)	-	48h EC50: = 0.03 mg/L
Iron 7439-89-6	-	96h LC50: 13.6 mg/L (Morone saxatilis)	-	-
Nickel 7440-02-0	72h EC50: = 0.18 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 0.174 - 0.311 mg/L (Pseudokirchneriella subcapitata)	96h LC50: > 100 mg/L (Brachydanio rerio) 96h LC50: 1.3 mg/L (Cyprinus carpio) 96h LC50: 10.4mg/L (Cyprinus carpio)	-	48h EC50: > 100 mg/L 48h EC50: 1 mg/L
Carbon black 1333-86-4	-	-	-	24h EC50: > 5600 mg/L

Persistence and Degradability	No information available.
Bioaccumulation	No information available
Other adverse effects	No information available.

Section 13 – Disposal Considerations

Waste treatment methods

Disposal methods: This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging: Dispose of in accordance with federal, state and local regulations.

Chemical Name	RCRA	RCRA - D Series Wastes	RCRA - U Series Wastes	OSHA
Nickel 7440-02-0	(hazardous constituent - no waste number)	Included in waste streams: F006, F039	-	-

California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Copper 7440-50-8	Toxic
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	Toxic
Nickel 7440-02-0	Toxic powder Ignitable powder
Aluminum 7429-90-5	Ignitable powder

Section 14 – Transport Information

The Li-ion Battery Pack as stated in Appendix is made in compliance to the requirements stated in the latest edition of the IATA Dangerous Goods Regulations Packing Instruction 965 section IB or 966 section II or 967 section II.

With regard to transport, the following regulations are cited and considered:

- The International Civil Aviation Organization (ICAO) Technical Instructions, Packing instruction 965 section IB or 966 section II or 967 section II (2023-2024 Edition).
- The International Air transport Association (IATA) Dangerous Goods Regulations, Packing instruction 965 section IB or 966 section II or 967 section II (64th Edition, 2023).
- Special provision 188 of the International Maritime Dangerous Goods (IMDG) Code (Amendment 40-20 Edition).
- The US Hazardous Materials Regulation 49 CRF (Code of Federal Regulations), sections 173-185 Lithium batteries and cells.
- The UN Recommendations on the Transport of Dangerous Goods, Manual of Tests and Criteria 38.3 Lithium batteries.

These products are properly classified, described, packaged, marked, and labeled, and are in proper condition for transportation according to all the applicable international and national governmental regulations, not limited to the above mentioned. We further certify that the enclosed products have been tested and fulfilled the requirements and conditions in accordance with UN Recommendations (T1 – T8) on the Transport of Dangerous Goods Model Regulations and the Manual of Tests and Criteria.

Test results of the UN Recommendation on the Transport of Dangerous Goods

Manual of Test and Criteria (38.3 Lithium battery)			
No.	Test items	Test results	Remark
T1	Altitude simulation	Pass	-
T2	Thermal test	Pass	-
T3	Vibration	Pass	-
T4	Shock	Pass	-
T5	External short circuit	Pass	-
T6	Impact	Pass	-
T7	Overcharge	Pass	-
T8	Forced discharge	Pass	-

Additional Requirements for air transport:

1. Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.
2. Cells and batteries must be manufactured under a quality management program.
3. The Watt-hour rating must be marked on the outside of the battery case except those manufactured before 1 January 2009.
4. Cells and batteries must be packed in strong outer packagings. (Applicable to PI 965 only)
5. Cells and batteries must be packed in inner packagings that completely enclose the cell or battery. To provide protection from damage or compression to the batteries, the inner packagings must be placed in a strong rigid outer packaging of one of the packaging types shown below.
6. Each consignment must be accompanied with a document with an indication that:
 - the package contains lithium ion cells or batteries;
 - the package must be handled with care and that a flammability hazard exists if the package is damaged;
 - special procedures must be followed in the event the package is damaged, to include inspection and repacking if necessary; and
 - a telephone number for additional information.
7. Each package must be labelled with a lithium battery handling label (Figure 7.4.H) in addition to the Class 9 hazard label (Figure 7.3.W) and Cargo Aircraft Only label.
Each package must be marked in accordance with the requirements of 7.1.4.1(a) and (b) and in addition the net weight when required by 7.1.4.1(c) must be marked on the package. (Applicable to PI 965 only)
8. Each package must be capable of withstanding a 1.2 m drop test in any orientation without (Applicable to PI 965 and 966 only):
 - damage to cells or batteries contained therein;
 - shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - release of contents.
9. Each package must be labelled with a lithium battery handling label (Figure 7.4.H). (Applicable to PI 966 and 967 only)

10. A Shipper's Declaration for Dangerous Goods is not required. (Applicable to PI 966 and 967 only)
11. Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.
12. The equipment must be secured against movement within the outer packaging and must be equipped with an effective means of preventing accidental activation. (Applicable to PI 966 only)
13. The maximum number of batteries in each package must be the minimum number required to power the equipment plus two spares. (Applicable to PI 966 only)
14. The words "Lithium ion batteries in compliance with Section II of PI 966" must be included on the air waybill, when an air waybill is used. The information should be shown in the "Nature and Quantity of Goods" box of the air waybill. (Applicable to PI 966 only)
15. Maximum net quantity of lithium ion cells must not be more than 5 kg. (Applicable to PI 966 and 967 only)
16. Equipment must be equipped with an effective means of preventing accidental activation. (Applicable to PI 967 only)
17. The equipment containing the cells or batteries must be secured against movement within the outer packaging and be packed so as to prevent accidental operation during air transport. (Applicable to PI 967 only)
18. The equipment must be packed in strong outer packagings constructed of suitable material of adequate strength and design in relation to the packaging's capacity and its intended use unless the cell or battery is afforded equivalent protection by the equipment in which it is contained. (Applicable to PI 967 only)
19. Where a consignment includes packages bearing the lithium battery handling label, the words "Lithium ion batteries in compliance with Section II of PI 967" must be included on the air waybill, when an air waybill is used. The information should be shown in the "Nature and Quantity of Goods" box of the air waybill. (Applicable to PI 967 only)

Section 15 - Regulatory Information

International Inventories

TSCA: Complies

DSL: All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Copper	7440-50-8	5~15	1.0
Lithium Cobalt Oxide (LiCoO ₂)	12190-79-3	1~5	0.1
Nickel	7440-02-0	0.1~1	0.1
Aluminum	7429-90-5	1~5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	No
---------------------	----

Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8	-	X	X	-
Nickel 7440-02-0	-	X	X	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper 7440-50-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Nickel 7440-02-0	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Nickel - 7440-02-0	Carcinogen
Carbon black - 1333-86-4	Carcinogen
Lithium carbonate - 554-13-2	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Graphite 7782-42-5	X	X	X	-	-
Dimethyl carbonate 616-38-6	X	X	X	-	-
Copper 7440-50-8	X	X	X	X	X
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	X	-	X	X	X

Nickel 7440-02-0	X	X	X	X	X
Carbon black 1333-86-4	X	X	X	-	X
Aluminum 7429-90-5	X	X	X	X	-
Lithium carbonate 554-13-2	X	X	-	X	-

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Graphite 7782-42-5 (20~30%)	-	Mexico: TWA= 2 mg/m ³
Copper 7440-50-8 (5~15%)	-	Mexico: TWA= 1 mg/m ³ Mexico: TWA= 0.2 mg/m ³ Mexico: STEL= 2 mg/m ³
Nickel 7440-02-0 (0.1~1%)	-	Mexico: TWA 1 mg/m ³
Carbon black 1333-86-4 (0.1~1%)	-	Mexico: TWA 3.5 mg/m ³ Mexico: STEL 7 mg/m ³
Aluminum 7429-90-5 (1~5%)	-	Mexico: TWA= 10 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

Non-controlled

Section 16 - Other Information

NFPA	Health Hazards 1	Flammability 0	Instability 1	Physical and Chemical Hazards - Personal Protection X
HMIS	Health Hazards 4	Flammability 0	Physical Hazard 1	

Revision Note: No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

--End of Safety Data Sheet--